

TETHA BLOQ 2M SELF RETRACTING LIFELINE

C/W 1 X TRIPLE ACTION KARABINER AND 1 X DOUBLE ACTION SCAFF HOOK

PART CODE: **IRW200TBKTS**



Engineered for extreme workplace situation's, the TETHA BLOQ has been developed to be durable and lightweight. It extends and retracts automatically, allowing the user to operate within the recommended work area permitted by the AS/NZS Standard. The TETHA BLOQ maintains tension which clears the work zone of any loose and dangerous excess webbing. In the event of a fall, a brake activates, arresting the fall and reducing the impact of the fall to the worker. Best of all, the TETHA BLOQ is designed with a transparent outer casing, allowing users to perform before and after inspections more efficiently by simply seeing the inner workings and webbing inside the casing.

PRODUCT FEATURES >

- 1. Grey transparent outer casing made from high impact and UV resistant polycarbonate.
- 2. Triple action steel karabiner on top meets requirements of AS 1891.5:2020 > 6kN gate strength.
- 3. Dual stainless steel rollers built into casing to reduce friction on webbing and unnecessary fraying against outer casing.
- 4. ANSI steel scaff hook on bottom.
- Comes with built in energy absorber with protective cover.
- Allows workers to use in horizontal and foot level anchorage applications.
- Swivel attachment point on top on SRL.
- Reduces impact forces to less than 6kN.
- Rated for up to 140kg worker.
- Retractable webbing maximum length: 2m
- Full service not required - refer to user instructions.

APPLICATIONS >

Scaffolding, Construction, Utilities, EWP, Warehouse, Mining.

STANDARDS >

- Certified to standard EN 360:2002
- Accepted under AS/NZS 1891.3:2020 refer to table 1 – Acceptance of systems conforming to international standards.

TECHNICAL INFORMATION >

- Webbing:** Polyester
- Width:** 25mm
- Thickness:** 1.5mm
- Breaking Strength:** 20kN (Min.)
- Energy Absorber:** Polyamide tear webbing

Vital Test Compliance:

- Static Strength:** 15kN for 3 minutes
- Dynamic Performance:** Maximum breaking force does not exceed 6kN in the line when tested on a free-falling mass of 140kgs.



LINQ may make improvements and/or changes in the products described in this information at any time without notice. Please use in accordance with Product User Guide.

LINQ HEIGHT SAFETY

2/980 ABERNETHY ROAD,
HIGH WYCOMBE, WA 6057
TECH SUPPORT: 1300 546 747
CUSTOMER SERVICE: 1300 770 723
EMAIL: INFO@PARAMOUNTSAFETY.COM

LINQ HEIGHT SAFETY NEW ZEALAND

7 SIR WOOLF FISHER DRIVE, Highbrook,
EAST TAMAKI, AUCKLAND 2013
TECH SUPPORT: 0800 546 747
CUSTOMER SERVICE: 0800 888 778
EMAIL: INFO@PARAMOUNTSAFETY.CO.NZ

WWW.LINQHS.COM
WWW.PIPANZ.COM

